# LogiLink®

www.LogiLink.de

**Art No. WL0237**

# WLAN 802.11ac Nano USB Adapter

**Feature:**
- Ultra-Nano size design
- Complies with IEEE802.11 ac/a/b/g/n standards
- Built-in 2dbi Planar Inverted-F Antenna (PIFA)
- 600 Mbps Dual Band (2,4GHz / 5GHz)
- Data transfer rate up to 150Mbps (2,4GHz) or up to 433Mbps (5GHz)
- Supports 64/128-bit WEP, WPA, WPA2, WPA-PSK, TKIP, AES Encryption
- Supports USB 2.0/1.1 interface
- Supports Windows XP/Vista/7/8/8.1
      Linux Kernel 2.6.18~2.6.38 and 3.8.2
      MAC OS X 10.4/10.5/10.6/10.7/10.8/10.10
      Android 1.6~2.3/4.0~4.2

**Specifications:**

| | |
|---|---|
| Chipset Solution | Realtek 8811AU |
| Standard | IEEE802.11 ac/a/b/g/n |
| Interface Type | USB 2.0 /1.1 |
| Frequency Band | 2,4000~2,4835GHz (varies according to different regions) |
| Data Rate | 150Mbps (2,4GHz) 433Mbps (5GHz) |
| Transmit Power | 18dBm (EIRP) |
| Power Consumption | 0,75W |
| Transmission Distance | 10-15m |
| Security | 64/128-bit WEP, WPA, WPA2, WPA-PSK, TKIP, AES |
| Supported OS | Windows XP/Vista/7/8/8.1 Linux Kernel 2.6.18~2.6.38 and 3.8.2 MAC OS X 10.4/10.5/10.6/10.7/10.8/10.10 Android 1.6~2.3/4.0~4.2 |

WL0237

RoHS compliant  CE

4 052792 035025

Made in China

# LogiLink®

www.LogiLink.de

**Art No. WL0237**

# WLAN 802.11ac Nano USB Adapter

| Dimension | 22 x 16,4 x 8,5mm |
|---|---|
| Weight | 2,4g |
| Temperature | Operating Temperature: 0°C~40°C<br>Storage Temperature: -20~60°C |
| Humidity | Operating Humidity: 10%~85% non-condensing<br>Storage Humidity: 5%~95% non-condensing |

**Package Contents:**
- 1 x WLAN 802.11ac Nano USB Adapter
- 1 x Quick Installation Guide
- 1 x CD

**Packaging Information:**
- Package Dimension: 107 x 164 x 25mm
- Package Weight: 0,05kg
- Carton Q'ty: 200pcs
- Carton Dimension: 600 x 260 x 335mm
- Carton Weight: 8,8kg

WL0237

RoHS compliant    CE

4 052792 035025

Made in China

*The specifications and pictures are subject to change without notice.
*All trade names referenced are the registered namework of their respective owners.