

REVISION RECORD

REV	ECN	DESCRIPTION	DRFT	DATE
-----	-----	-------------	------	------

NOTES1:

- UL Standard
- 1.Rated voltage/current : 300V / 8A
- 2.Withstanding voltage : AC1600V/1Min.
- 3.Torque value : M2 , 1.77Lb.in
- 4.Wire range : 28~16AWG

IEC Standard

1. Pollution degree	2
Overvoltage category	II
Rate impulse voltage(KV)	2.5KV
Rate voltage(V)	250V
Rate current(A)	7A

- 2.Torque value : M2 , 0.2N·m
- 3.Wire range : 0.5~1.5mm<sup>2</sup>

NOTES2:

- 1.Dimension shall be interpreted per ASME Y14.5-2009
- 2.Pitch : 3.5/3.81mm, Poles : N=02~24P
- 3.Stripping length : 6~7mm
- 4.Operating temperature: -40°C~+105°C
- 5.Undimensioned tolerances:



Pitch range in mm		Nominal dimension range in mm						0.1/10
Over 6 TO 10	Over 10 TO 24	Over 30 TO 60	Over 60 TO 100	Over 100 TO 150	Over 150		0.1/10	
±0.15	±0.20	±0.30	±0.50	±0.70	±1.00	±1.30	±2*	

6.RoHS Compliance

15EDGK - 3.5/3.81 - XXP - 1Y - 00A (H)

(Series No.) (Pitch) (Poles) (Color): 1.(Grey)  
 2.(Blue)  
 3.(Black)  
 4.(Green)  
 5.(Orange)  
 6.(Red)  
 7.(Transparent)  
 8.(Yellow)  
 9.(White)

(RoHS)  
 00A--(Standard)







2.15  
2.30

3.5  
3.81

3.5x(N-1)  
3.81x(N-1)

3.5x(N-1)+4.3  
3.81x(N-1)+4.6

02~06P have this card point



DETACHED LISTS	PART NO.:	/		
	APPD:	/		
	CHKD:	/		
	DRFT:	/		
	NAME:		15EDGK-3.5/3.81-XXP-1Y-00A(H)	
TITLE:		CUSTOMER DRAWING	REV	DO
DRAWING NO.:		/	SHEET	1/1
THIRD ANGLE PROJECTION		MM (INCH)	DO NOT SCALE DRAWING	SCALE 1:1

宁波高松电子有限公司  
 NINGBO DEGSON ELECTRICAL CO., LTD

15EDGK-3.5/3.81-XXP-1Y-00A(H)

CUSTOMER DRAWING REV DO

DRAWING NO.: / SHEET 1/1

MM (INCH) DO NOT SCALE DRAWING SCALE 1:1