



PRODUCT SPEC SHEET

SKU 23849

Model:VT-4949-FC-S

EAN:3800170228986

VT-4949-FC 50W LED FAST CONNECTOR FLOODLIGHT PIR SENSOR 6500K BLACK BODY 120LM/W



IP65
STANDARD

02 YEAR
WARRANTY

Super Bright
120
LUMENS/W

- High quality Slim series Floodlight with PIR Sensor and Fast Connector
- Designed with high efficiency SMD Chips
- In-built junction box for direct plugin
- Powerful LED light source with high lumen efficiency of 120 LM/W
- 3-8m (Radius) Detection Distance
- Built Strong and durable with Aluminium - Corrosion resistant design
- Perfectly built for outdoor with Ingress protection of IP65
- Application - Facade lighting, lobby, garage, passage, parking lot and many more

TECHNICAL INFORMATION

| | |
|------------------------|----------------------|
| Dimmable: | No |
| Color Temperature: | 6500K |
| Model: | VT-4949-FC-S |
| Watts: | 50 |
| Lumens: | 6000 |
| Input Power: | AC:220-240V, 50/60Hz |
| Unit Color: | Black |
| Color for Web: | White |
| Body Type: | Aluminium |
| Dimension: | 217.3x89.1x241.9mm |
| Operation Temperature: | -20°C to +45°C |
| Instant Start: | 0-100% in <1s |
| Detection Range: | 120°±20° |
| Time Delay: | Min 7sec+2sec Max |

LISTING DETAILS

| | |
|-----------------|---------------|
| SKU: | 23849 |
| Model: | VT-4949-FC-S |
| EAN: | 3800170228986 |
| Commodity Code: | 94054210 |

PACKAGING

| | |
|---------------------|--------------------|
| Gross Weight (Kgs): | 0.75 |
| Unit CBM: | 0.004117 |
| Dimension: | 217.3x89.1x241.9mm |

MASTER BOX PACKAGING

| | |
|------------------|-----|
| Box Qty: | 20 |
| Qty Per Pallet: | |
| Length (Box) mm: | 221 |

| | |
|----------------------|---------------|
| | 7min+2min |
| PF: | >0.9 |
| LED Chip Type: | SMD |
| Beam Angle: | 120° |
| Detection Distance: | 3-8m (Radius) |
| CRI: | >70 |
| Energy Rating Label: | E (2021) |
| IP Rating: | IP65 |
| Long Life: | 25,000 Hours |
| Energy Saving: | 85 Energy |
| Sensor Type: | PIR |
| lumens per watt: | 120 |

| | |
|------------------|-----|
| Width (Box) mm: | 72 |
| Height (Box) mm: | 220 |