| | I | | 50 | | | | 3 | 1 | Ľ |
|-------------------|---|--|----|--|--|--|---|---|---|
| - 15 € | | | | | | | | 1 | - |

Product: Flex SMD LED Strip

Part Number: 3528Ux-330-12VWF

| Emitting Color: | Red | Yellow | Green | Blue | White | | | | |
|------------------------|----------------------------|------------------|---------|---------|-------------|--|--|--|--|
| Wavelength (nm): | 620-635 | 584-596 | 515-525 | 460-475 | X=0.3 Y=0.3 | | | | |
| 50% Power Angle (2θ½): | 120° | 120 | 120° | 120° | 120° | | | | |
| Intensity (mcd): | 300 | 300 | 800 | 200 | 800 | | | | |
| Lumen (lm): | 200 | 200 | 680 | 200 | 660 | | | | |
| Power Consumption: | | , | Acres 1 | | | | | | |
| Operating Voltage: | DC 12V | | | | | | | | |
| Current: | | 450 mA | | | | | | | |
| Dimension: | | L×W×H=1000×8×2mm | | | | | | | |
| LED Quantity: | 66 pcs | | | | | | | | |
| Using Temperature | -20℃~60℃ | | | | | | | | |
| Protection Level | IP65 | | | | | | | | |
| Approval | CE (NO:E8 06 01 57489 001) | | | | | | | | |

Attractive Features:

The application of soft & flexible PCB makes the strip possible to be bent into any shape as per users' needs. The viewing angle as wide as 120° and adjustable length by cutting off or connecting every three LEDs enable it to be more suitable for the applications of signs, advertisings and backlights.

Other Feature:

- 1. Emitting Color: Red, Yellow, Green, Blue, White, etc.
- 2. Unique circuit design with strong resistance against static electricity ensures the stability
- 3. Application: Channel Letters, Decoration, Sign Illumination, especially for channel letter
- 4. CE approved & RoHS compliant