



Socket AM2+/AM2

Supports AMD Phenom II/Phenom/Athlon 64 X2/64/FX/Sempron Processors

Hyper Transport Technology up to 2G

Supports AMD Cool'n'Quiet Technology

It is recommended to use 95w CPU

Chipset	NVIDIA GeForce 6150 / nforce430a				
HIGHLIGHTS	 AM3/AM2 ⁺	 X.D.C	 BIOS-Flasher	 BIOS-ReLife	
MAIN	 RoHS	 HT2G	 DUAL DDR2	 PCI-E	 LAN
	 6 Channel HD AUDIO	 SATA2	 IDE	 RAID	 USB2.0
CPU SUPPORT	AMD Phenom™ II X4 Processor AMD Phenom™ II X3 Processor AMD Phenom™ X4 Processor AMD Phenom™ X3 Processor AMD Athlon™ X2 Dual-Core Processor AMD Athlon™ 64 X2 Dual-Core Processor AMD Athlon™ 64 FX Processor AMD Athlon™ 64 Processor AMD Sempron™ Processor				
HT	Support HT 2G				
MEMORY	Support Dual Channel DDR2 533/667/800 MHz 2 x DDR2 DIMM Memory Slot Max. Supports up to 4GB Memory				

EXPANSION SLOT	1 x PCI Slots 1 x PCI-E x16 Slot
STORAGE	2 x SATA2 3Gb/s Connector 1 x IDE Connector Support SATA RAID: 0,1
USB	4 x USB 2.0 Port 2 x USB 2.0 Header
LAN	Realtek RTL8201CL - 10/100 PHY
INTEGRATED VIDEO	NVIDIA GeForce 6150 GPU, On Board Graphic Max. Memory Share Up to 512MB(Under OS By Turbo Cache)
CODEC	Realtek ALC662 6-Channel HD Audio
REAR I/O	 1 x PS/2 Mouse 1 x PS/2 Keyboard 4 x USB 2.0 Port 1 x VGA Port 1 x RJ-45 Port 3 x Audio Connector
INTERNAL I/O	1 x Printer Header 2 x USB 2.0 Header 2 x SATA2 3Gb/s Connector 1 x IDE Connector 1 x Floppy Connector 1 x Front Audio Header 1 x Front Panel Header 1 x CPU FAN Header 1 x System FAN Header
DIMENSION	Micro ATX Form Factor Dimension: 23.5cm X 17cm (W x L)
OS SUPPORT	Support Windows XP / XP 64 / Vista / Vista 64
ACCESSORIES	1 x IDE Cable 1 x SATA Cable 1 x I/O Shield 1 x CD Driver 1 x User Manual