



Socket AM2+/AM2

Supports AMD Phenom II/Phenom/Athlon 64 X2/64/FX/Sempron Processors

Hyper Transport Technology up to 2G

Supports AMD Cool'n'Quiet Technology

It is recommended to use 95w CPU

Chipset	NVIDIA GeForce 6150 / nforce430a			
HIGHLIGHTS	 AM3/AM2 ⁺	 X.D.C	 BIOS-Flasher	 BIOS-ReLife
MAIN	 RoHS	 HT2G	 DUAL DDR2	 PCI-E
	 6 Channel HD AUDIO	 SATA2	 IDE	 RAID
	 USB2.0			
CPU SUPPORT	☐ AMD Phenom™ II X4 Processor ☐ AMD Phenom™ II X3 Processor ☐ AMD Phenom™ X4 Processor ☐ AMD Phenom™ X3 Processor ☐ AMD Athlon™ X2 Dual-Core Processor ☐ AMD Athlon™ 64 X2 Dual-Core Processor ☐ AMD Athlon™ 64 FX Processor ☐ AMD Athlon™ 64 Processor ☐ AMD Sempron™ Processor			
HT	☐ Support HT 2G			
MEMORY	☐ Support Dual Channel DDR2 533/667/800 MHz ☐ 2 x DDR2 DIMM Memory Slot ☐ Max. Supports up to 4GB Memory			

EXPANSION SLOT	☐ 1 x PCI Slots ☐ 1 x PCI-E x16 Slot
STORAGE	☐ 2 x SATA2 3Gb/s Connector ☐ 1 x IDE Connector ☐ Support SATA RAID: 0,1
USB	☐ 4 x USB 2.0 Port ☐ 2 x USB 2.0 Header
LAN	☐ Realtek RTL8201CL - 10/100 PHY
INTEGRATED VIDEO	☐ NVIDIA GeForce 6150 GPU, On Board Graphic Max. Memory Share Up to 512MB(Under OS By Turbo Cache)
CODEC	☐ Realtek ALC662 6-Channel HD Audio
REAR I/O	 ☐ 1 x PS/2 Mouse ☐ 1 x PS/2 Keyboard ☐ 4 x USB 2.0 Port ☐ 1 x VGA Port ☐ 1 x RJ-45 Port ☐ 3 x Audio Connector
INTERNAL I/O	☐ 1 x Printer Header ☐ 2 x USB 2.0 Header ☐ 2 x SATA2 3Gb/s Connector ☐ 1 x IDE Connector ☐ 1 x Floppy Connector ☐ 1 x Front Audio Header ☐ 1 x Front Panel Header ☐ 1 x CPU FAN Header ☐ 1 x System FAN Header
DIMENSION	☐ Micro ATX Form Factor Dimension: 23.5cm X 17cm (W x L)
OS SUPPORT	☐ Support Windows XP / XP 64 / Vista / Vista 64
ACCESSORIES	☐ 1 x IDE Cable ☐ 1 x SATA Cable ☐ 1 x I/O Shield ☐ 1 x CD Driver ☐ 1 x User Manual