

WD Caviar[®] Green[™]

Desktop Hard Drives

As hard drive capacities increase, the power required to run those drives increases as well. WD Caviar Green drives make it possible for energy-conscious customers to build systems with higher capacities and the right balance of system performance, ensured reliability, and energy conservation.

INTERFACE

SATA

WIDTH/HEIGHT 3.5-inch/1-inch

MODEL NUMBERS

WD30EZRX WD30EZRSDTL WD25EZRX WD25EZRSDTL WD20EARX WD20EARS

WD15EARX WD15EARS WD10EARS WD7500AARS WD7500AADS

Product Features

Massive capacity

WD Caviar Green SATA drives now deliver up to 3 TB of storage on a single drive.

Reduced power consumption WD has reduced power consumption making it possible for our energyconscious customers to build systems with higher capacities and the right balance of system performance, ensured reliability, and energy conservation.

Cool and quiet

Drives with WD GreenPower Technology™ yield lower operating temperatures for increased reliability and low acoustics for ultra-quiet PCs and external drives.

Perfect for external drives

External drive manufacturers can eliminate the need for a fan in a high-capacity product with a WD Caviar Green drive, the coolest and quietest in its class.

IntelliPower

IntelliPower™

A fine-tuned balance of spin speed, transfer rate, and caching algorithms designed to deliver both significant power savings and solid performance. Additionally, WD Caviar Green drives consume less current during startup allowing lower peak loads on systems as they are booted.

IntelliSeek™

Calculates optimum seek speeds to lower power consumption, noise, and vibration

NoTouch™ ramp load technology

Note: Not all products may be

available in all regions of the world.

The recording head never touches the disk media ensuring significantly less wear to the recording head and media as well as better drive protection in transit

Advanced Format (AF)

Technology being adopted by WD and other drive manufacturers as one of multiple ways to continue growing hard drive capacities. AF is a more efficient media format that enables increased areal densities. (RX, RS, and RSDTL models only)

Applications

Desktop PCs, high capacity external storage, and NAS.

Desktop / Consumer RAID Environments - WD Caviar Green Hard Drives are tested and recommended for use in consumer-type RAID applications (RAID-0 / RAID-1).

Business Critical RAID Environments – WD Caviar Green Hard Drives are not recommended for and are not warranted for use in RAID environments utilizing Enterprise HBAs and/or expanders and in multi-bay chassis, as they are not designed for, nor tested in, these specific types of RAID applications. For all Business Critical RAID applications, please consider WD's Enterprise Hard Drives that are specifically designed with RAID-specific, time-limited error recovery (TLER), are tested extensively in 24x7 RAID applications, and include features like enhanced RAFF technology and thermal extended burn-in testing.







WD Caviar Green

Specifications'	3 TB	3 TB	2.5 TB	2.5 TB	2 TB	2 TB
Model number	WD30EZRX	WD30EZRSDTL	WD25EZRX	WD25EZRSDTL	WD20EARX	WD20EARS
Interface	SATA 6 Gb/s	SATA 3 Gb/s	SATA 6 Gb/s	SATA 3 Gb/s	SATA 6Gb/s	SATA 3 Gb/s
Formatted capacity	3,000,592 MB	3,000,592 MB	2,500,495 MB	2,500,495 MB	2,000,398 MB	2,000,398 MB
User sectors per drive	5,860,533,168	5,860,533,168	4,883,781,168	4,883,781,168	3,907,029,168	3,907,029,168
Advanced Format (AF)	Yes	Yes	Yes	Yes	Yes	Yes
SATA latching connector	Yes	Yes	Yes	Yes	Yes	Yes
Form factor	3.5-inch	3.5-inch	3.5-inch	3.5-inch	3.5-inch	3.5-inch
RoHS compliant ²	Yes	Yes	Yes	Yes	Yes	Yes
Performance						
Data transfer rate (max) Buffer to host Host to/from drive (sustained)	6 Gb/s 123 MB/s	3 Gb/s 123 MB/s	6 Gb/s 123 MB/s	3 Gb/s 123 MB/s	6 Gb/s 110 MB/s	3 Gb/s 110 MB/s
Cache (MB)	64	64	64	64	64	64
Rotational speed (RPM)	IntelliPower	IntelliPower	IntelliPower	IntelliPower	IntelliPower	IntelliPower
Reliability/Data Integrity						
Load/unload cycles ³	300,000	300,000	300,000	300,000	300,000	300,000
Non-recoverable read errors per bits read	<1 in 1014	<1 in 1014	<1 in 1014	<1 in 10 ¹⁴	<1 in 10 ¹⁴	<1 in 10 ¹⁴
Limited warranty (years) ⁴	3	3	3	3	3	3
Power Management						
12VDC (A, peak)	1.78	1.78	1.78	1.78	1.75	1.75
Average power requirements (W) Read/write Idle Standby Sleep	6 5.5 0.8 0.8	6 5.5 0.8 0.8	6 5.5 0.8 0.8	6 5.5 0.8 0.8	4.5 2.5 0.7 0.7	4.5 2.5 0.7 0.7
Environmental Specifications ⁵						
Temperature (°C) Operating Non-operating	0 to 60 -40 to 70	0 to 60 -40 to 70				
Shock (Gs) Operating (2 ms, read) Operating (2 ms, read/write) Non-operating (1 ms)	30 65 250	30 65 250	30 65 250	30 65 250	30 65 250	30 65 250
Average acoustics (dBA) ^b Idle mode Performance seek mode Quiet seek mode	24 29 25	24 29 25	24 29 25	24 29 25	24 29 25	24 29 25
Physical Dimensions						
Height (in./mm, max)	1.028/25.4	1.028/25.4	1.028/25.4	1.028/25.4	1.028/25.4	1.028/25.4
Length (in./mm, max)	5.787/147	5.787/147	5.787/147	5.787/147	5.787/147	5.787/147
Width (in./mm, $\pm .01$ in.)	4/101.6	4/101.6	4/101.6	4/101.6	4/101.6	4/101.6
Weight (lb./kg, ± 10%)	1.61/0.73	1.61/0.73	1.61/0.73	1.61/0.73	1.40/0.64	1.40/0.64

¹ As used for storage capacity, one megabyte (MB) = one million bytes, one gigabyte (GB) = one billion bytes, and one terabyte (TB) = one trillion bytes. Total accessible capacity varies depending on operating environment. As used for buffer or cache, one megabyte (MB) = 1,048,576 bytes. Sa used for transfer rate or interface, megabyte per second (MB/s) = one million bytes per second, and gigabit per second (GB/s) = one billion bits per second. Effective maximum SATA 3 Gb/s transfer rate calculated according to the Serial ATA specification published by the SATA-ID or drive products manufactured and soid worldwide after June 1, 2006, meet or exceed Restriction of Hazardous Substances (RoHS) compliance requirements as mandated by the European Union for electrical and electronic products. The RoHS Directive 2002/95/EC of the European Parlament, which is effective in the EU beginning July 1, 2006, aims to protect human health and the environment by restricting the use of certain hazardous substances in new equipment, and consists of restrictions on lead, mercury, cadmium, and other substances. ³Controlled unload at ambient condition

⁴The term of the limited warranty may vary by region. Visit support.wdc.com/warranty for details.

 $^{5}\mathrm{No}$ non-recoverable errors during operating tests or after non-operating tests.

⁶Sound power level.



WD Caviar Green

Specifications ¹	1.5 TB	1.5 TB	1 TB	750 GB	750 GB
Model number	WD15EARX	WD15EARS	WD10EARS	WD7500AARS	WD7500AADS
Interface	SATA 6 Gb/s	SATA 3 Gb/s	SATA 3 Gb/s	SATA 3 Gb/s	SATA 3 Gb/s
Formatted capacity	1,500,301 MB	1,500,301 MB	1,000,204 MB	750,156 MB	750,156 MB
User sectors per drive	2,930,277,168	2,930,277,168	1,953,525,168	1,465,149,168	1,465,149,168
Advanced Format (AF)	Yes	Yes	Yes	Yes	No
SATA latching connector	Yes	Yes	Yes	Yes	Yes
Form factor	3.5-inch	3.5-inch	3.5-inch	3.5-inch	3.5-inch
RoHS compliant ²	Yes	Yes	Yes	Yes	Yes
Performance					
Data transfer rate (max) Buffer to host Host to/from drive (sustained)	6 Gb/s 110 MB/s	3 Gb/s 110 MB/s	3 Gb/s 110 MB/s	3 Gb/s 110 MB/s	3 Gb/s 110 MB/s
Cache (MB)	64	64	64	64	32
Rotational speed (RPM)	IntelliPower	IntelliPower	IntelliPower	IntelliPower	IntelliPower
Reliability/Data Integrity					
Load/unload cycles ³	300,000	300,000	300,000	300,000	300,000
Non-recoverable read errors per bits read	<1 in 10 ¹⁴				
Limited warranty (years) ⁴	3	3	3	3	3
Power Management					
12VDC (A, peak)	1.75	1.75	1.47	1.47	1.47
Average power requirements (W) Read/write Idle Standby Sleep	4.5 2.5 0.7 0.7	4.5 2.5 0.7 0.7	4.9 2.8 0.4 0.4	4.9 2.8 0.4 0.4	4.9 2.8 0.4 0.4
Environmental Specifications ⁵					
Temperature (°C) Operating Non-operating	0 to 60 -40 to 70				
Shock (Gs) Operating (2 ms, read) Operating (2 ms, read/write) Non-operating (1 ms)	30 65 250	30 65 250	30 65 300	30 65 300	30 65 300
Average acoustics (dBA) ^b Idle mode Performance seek mode Quiet seek mode	24 29 25	24 29 25	23 27 24	23 27 24	23 27 24
Physical Dimensions					
Height (in./mm, max)	1.028/25.4	1.028/25.4	1.028/25.4	1.028/25.4	1.028/25.4
Length (in./mm, max)	5.787/147	5.787/147	5.787/147	5.787/147	5.787/147
Width (in./mm, ± .01 in.)	4/101.6	4/101.6	4/101.6	4/101.6	4/101.6
Weight (lb./kg, ± 10%)	1.40/0.64	1.40/0.64	1.32/0.60	1.32/0.60	1.32/0.60

¹As used for storage capacity, one megabyte (MB) = one million bytes, one gigabyte (GB) = one billion bytes, and one terabyte (TB) = one trillion bytes. Total accessible capacity varies depending on operating environment. As used for buffer or cache, one megabyte (MB) = 1,048,576 bytes. As used for transfer rate or interface, megabyte per second, MB/s) = one million bytes per second. And gigabit per second (MB/s) = one billion bits per second (MB/s) = one billion bits per second. Bytes As used for transfer rate or interface, megabyte per second (MB/s) = one billion bytes per second. Effective maximum SATA 3 Gb/s transfer rate calculated according to the Serial ATA specification published by the SATA-10 or gior defaults.

³Controlled unload at ambient condition

⁴The term of the limited warranty may vary by region. Visit support.wdc.com/warranty for details.

ł

v

Ċ

 $^{5}\mathrm{No}$ non-recoverable errors during operating tests or after non-operating tests. ⁶Sound power level.

WD Caviar Green is part of WD's complete lineup of desktop hard drives.



Western Digital 3355 Michelson Drive, Suite 100 Irvine, California 92612 U.S.A.

For service and literature:								
http://support.wdc.com								
www.westerndigital.	com							
300.ASK.4WDC 300.832.4778 ⊧800.6008.6008 00800.27549338	North America Spanish Asia Pacific Europe							
⊦31.880062100	(toll free where Europe/Middle							



available)

Fast/Africa



WD Caviar Black **Desktop Hard Drives** Maximum performance for power computing.



Canada ICES-003 Class B / NMB-003 Classe B

Western Digital, WD, the WD logo, WD Caviar, and Put Your Life On It are registered trademarks in the U.S. and other countries; and WD Caviar Blue, WD Caviar Green, WD Caviar Black, IntelliSeek, IntelliPower, NoTouch, WD GreenPower Technology, and FIT Lab are trademarks of Western Digital Technologies, Inc. Other marks may be mentioned herein that belong to other companies. Product specifications subject to change without notice.

© 2011 Western Digital Technologies, Inc. All rights reserved.