

HW191DP



Computerbild 17/2006
Test Result: Good



LCD Panel

Input

Output

Power

Operating Condition

Physical

Controls

Certification

Extras 1 Extras 2 Extras 3 Accessories

HANNs.G

Display size	19" (48,26 cm) WIDE
Panel Type	Active Matrix TFT
Brightness	300 cd/m ² (typ.)
Contrast	700:1 (typ.)
Pixel pitch	0.283(H)*0.283(V) mm
Resolution (H x V)	WXGA+ 1440 x 900
Response time	5 ms (typ.)
View angles LR,UD	H/V 150°/135°
Display colors	16.2M Colors
Color	9300K, 6500K, User Mode
Display Surface	Anti-Glare
Input 1	D-Sub, Audio
Input 2	DVI-D
Input 3	
Output 1	
Output 2	
Headphone	
Speakers	1W x 2
Supply	AC 100~240V, 50~60Hz
Consumption	55 W
Temperature	5 ~ 35°C
Humidity	10 ~ 85%
Dimension (W*D*H)	453 x 198 x 380 mm
Packing dimension (W*D*H)	520 x 148 x 449 mm
Net weight	4,6 kg
Gross weight	6,3 kg
Tilt	0°~ 20°
Kensington Lock	✓
VESA mounting	VESA Standard, 100mm
Front control	Auto, Vol(-), Power/LED, Vol(+), Menu
On screen display	EN,TC,DE,FR,ES,IT,PT, NL,SC,JS,KR
Safety	UL/CUL, TUV, CB, BSMI, FCC, CE
Emission	TCO03
Power saving	EPA Energy Star
powercord, VGA cable, audio cable, users manual (CD), quickstart	

Specifications are subject to change without notice. Error accepted.

HANNspree Europe GmbH
Siemensring 66
47877 Willich
GERMANY
Tel: + 49 (0)2154/ 95 323-0
Fax: + 49 (0)2154/ 95 323-123
[http:// www.hannsg.com](http://www.hannsg.com)
info.europe@hannspree.com

GO BEYOND