



Art No. WC0016

## Outdoor IR IP Camera, H.264

### Feature:

- 1/3" H.R. CCD image sensor
- Resolution: NTSC: 768 (H) x 494 (V), PAL: 752 (H) x 582 (V)
- MPEG4, MPEG and H.264 compression
- True Day & Night surveillance with IR shifter & large aperture lens (F1.4)
- Outdoor IP Rating with IP67
- Longer IR effective distance up to 40 meters
- High resolution with the best video performance
- Smart Light Control to avoid overexposure
- Excellent outdoor ID design with cable management
- Durable 56 IR LEDs built-in application
- Motion detection and alarm notification via Email
- Supports 3G Mobile Phone Surveillance (iPhone, BlackBerry, WinCE, J2ME & Android, Symbian Support)
- Supports multiple access levels with password
- Supports up to 10 users on-line
- Complete IP surveillance system with Central Management System (CMS) software for up to 16 cameras at the same time

### Specification:

<b>• Environment</b>	
In/Out door use	Outdoor
Day/Night	Yes
<b>• Network</b>	
LAN Port	YES
LAN Connection	10/100 Based-T Ethernet
Frame Rate	NTSC: 30, PAL: 25
Number of Online Users	10
Network	With 3G Mobile Phone Surveillance
<b>• Video</b>	
Video Compression	H.264 / MPEG4 / MJPEG

**Remark:** For 3G Mobile Phone Surveillance, please download the mobile software installation for remote Surveillance via Mobile Phone or PDA from [www.logilink.com](http://www.logilink.com).

\* The specifications and pictures are subject to change without notice.  
 \*All trade names referenced are the registered namework of their respective owners.



RoHS  
compliant





Art No. WC0016

## Outdoor IR IP Camera, H.264

### Specification:

Video Remote Control	YES
Video Adjustment	Brightness, Contrast, Saturation and Hue
<b>• Camera</b>	
Image Sensor	1/3" HR color CCD image sensor
Pixels	NTSC: 768(H) x 494(V) / PAL: 752(H) x 582(V)
Min Illumination	0.05 Lux / F1.4, 0 Lux (IR ON)
Shutter Speed	1/60 (1/50) to 1/100,000 sec.
Lens	F1.4mm/f6.0mm
Viewing Angle	48°
IR LED	56 units
IR Effective Range	Up to 40 meters
Smart Light Control	YES
BLC	On/Off
White Balance	ATW
AGC	Auto
IRIS Mode	AES
IP Rating	IP67
<b>• Software</b>	
Supported Protocols	DDNS, PPPoE, DHCP, NTP, SNTP, TCP/IP, ICMP, SMTP, FTP, HTTP, RTP, RTSP
Security	Multiple user access levels with password protection
Web Management	The licensed software "Video Viewer" for up to 16 network cameras control simultaneously
Remote Control	YES
Motion Detection	YES
Alarm and event Notification	Image upload over FTP and Email
Mobile	Supports 3GPP mobile surveillance


\* The specifications are subject to change without notice.

\*\* Dimensional tolerance: (± 5mm)

\* The specifications and pictures are subject to change without notice.  
 \*\* All trade names referenced are the registered trademark of their respective owners.



RoHS  
compliant



Made in Taiwan



Art No. WC0016

## Outdoor IR IP Camera, H.264

### Specification:

<b>• Others</b>	
Power Source ( $\pm 10\%$ )	DC12V
Operating Temp.	0°C~40°C
Minimum Web Browsing Requirements:	<ul style="list-style-type: none"> <li>- Pentium 4 CPU 1.3 GHz or higher, or equivalent AMD</li> <li>- 256 MB RAM</li> <li>- AGP graphics card, Direct Draw, 32MB RAM</li> <li>- Windows 7, Vista, XP, Windows 2000 Server, ME, 98, DirectX 9.0 or later</li> <li>- Internet Explorer 6.x or later</li> </ul>

### Package contents

- 1 x Outdoor H.264 IR Network Camera
- 1 x RJ-45 Network Cable
- 1 x Bracket
- 1 x CD-ROM disc for user manual & licensed software "Video Viewer"

### Note:

- The DC12V 1A adapter & power cord are not included with the sales package. Please prepare yourself or order if necessary.

### Optional Accessories (Order separately if necessary)

- WC0016A: AC power adapter for WC0016

### Packaging Information:

- Packing Dimension: mm
- Packing Weight: kg
- Carton Dimension: mm
- Carton Q'ty: pcs
- Carton Weight: kg

