

CS1782A/CS1784A

2/4-Port USB DVI Dual Link KVMP™ Switch

The CS1782A/CS1784A USB DVI Dual Link KVMP™ Switch charts a revolutionary direction in KVM switch functionality. It combines the capabilities of a 2/4-port KVM switch with a 2-Port USB hub, while providing a DVI monitor interface and audio support. Moreover it carries advanced features, such as nVidia 3D Vision ready 120Hz 3D display support, gaming keyboard compatibility and port selection/switching using a mouse, aimed at giving you flexibility, convenience and enjoyment



Features

- 2-port DVI KVMP Switch with USB 2.0 and 7.1 Surround Sound Audio (CS1782A)
- 4-port DVÍ KVMP Switch with USB 2.0 and 2.1 Surround Sound Audio (CS1784A)
- One USB console controls two/four computers and two additional USB devices
- 2-port built in USB 2.0 hub fully compliant with the USB 2.0 specification
- Full bass response for high quality 7.1 channel surround sound systems (CS1782A)
- Full bass response for high quality 2.1 channel surround sound systems (CS1784A)
- Computer selection via front panel pushbuttons, hotkeys, and mouse

- Multiplatform support Windows, Linux, Mac, and Sun*
 Independent switching of KVM, USB, and Audio focus
 DVI digital and analog monitor support fully compliant with the DVI specifications
- Superior video quality: 1920 x 1200 @ 60Hz (Single Link); 2560 x 1600 @ 60Hz (Dual Link)

 • nVidia 3D Vision Ready: Works with 120Hz LCD monitors and active
- shutter glasses to create a 3D environment with maximum resolution of up to 1920 x 1080
- Support widescreen resolutions
- HDCP compatible
 Video DynaSync™ Exclusive ATEN technology that eliminates boot-up display problems and optimizes resolution when switching between ports
- Power on detection if one of the computers is powered off, the switch will automatically switch to the next powered-on computer
 Console mouse port emulation/bypass feature that supports most
- mouse drivers and multifunction mice
- Console keyboard emulation/bypass feature that supports most gaming / multimedia keyboards
- Complete keyboard emulation for error-free booting
 Mac/Sun keyboard support and emulation*
- Multilingual keyboard mapping supports English, Japanese, and French keyboards
- Auto Scań Mode for monitoring all computers
- Firmware upgradable
 - * PC keyboard combinations emulate Mac/Sun keyboards Mac/Sun keyboard work only with their own computers





Specification

Function				CS1782A	CS1784A
Computer Connections				2	4
Port Selection				Front Panel Pushbutt	ons, Hotkeys, Mouse
Connectors	Console Ports	Keyboard		1 x USB Type A Female (Black; rear panel)	
		Video		1 x DVI-I Female (White)	
		Mouse			ale (Black; rear panel)
		Audio	Line out	2 x Mini Stereo Jack Female (Green; 1 x front panel, 1 x rear panel)	
			Line in	1 x Mini Stereo Jack Female (Blue)	N/A
			Side Speaker out	1 x Mini Stereo Jack Female (Gray)	N/A
			Rear Speaker out	1 x Mini Stereo Jack Female (Black)	N/A
			Center / Subwoofer	1 x Mini Stereo Jack Female (Orange)	N/A
			Microphone	2 x Mini Stereo Jack Female (Pink; 1 x front panel, 1 x rear panel)	
	KVM Ports	Keyboard/ Mouse		2 x USB Type B Female (White)	4 x USB Type B Female (White)
		Video		2 x DVI-I Female (White)	4 x DVI-I Female (White
		Audio	Line out	2 x Mini Stereo Jack Female (Green)	4 x Mini Stereo Jack Female (Green)
			Line in	2 x Mini Stereo Jack Female (Blue)	N/A
			Side Speaker out	2 x Mini Stereo Jack Female (Gray)	N/A
			Rear Speaker out	2 x Mini Stereo Jack Female (Black)	N/A
			Center / Subwoofer	2 x Mini Stereo Jack Female (Orange)	N/A
			Microphone	2 x Mini Stereo Jack Female (Pink)	4 x Mini Stereo Jack Female (Pink)
	Power			1 x DC Jack	
	USB 2.0 Hub				Female (White; 1 x rear panel)
Switches	Selected			2 x Pushbutton	4 x Pushbutton
	On Line / Selected			2 (Orange)	4 (Orange)
LEDs	USB Link			2 (Green)	4 (Green)
Emulation	Keyboard	/ Mous	Δ		SB
Video				DVI Dual Link: 2560 x 1600 DVI Single Link: 1920 x 1200	
Scan Interval				1–99 secs. (5 secs. default)	
Power Consumption				DC 5.3V. 9 W	DC 5.3V, 10W
	Operating Temp.			0-50°C	
Environment	Storage Temp.			-20-60°C	
	Humidity			0–80% RH, Non-condensing	
Physical Properties	Housing			Metal	
	Weight			0.90 kg	0.93 kg
	Dimensions (L x W x H)				27.00 x 8.80 x 5.55 cm
	DITTICTION (EX W X II)			27.00 x 0.00 x 3.33 (III	27.00 x 0.00 x 3.33 (II

