

DIGITAL MULTIMETER

MS8360C / MS8360E

MS8360C

VOLTAGE AC 600V
DC 600V

CURRENT AC 10A
DC 10A



MS8360E

VOLTAGE AC 600V
DC 600V

CURRENT AC 10A
DC 10A



EMC
LVD



Specifications

MS8360C MS8360E

Specifications	Range	Accuracy	
DC Voltage	200mV/2V/20V/200V	±(0.5%+1)	±(0.5%+1)
	600V	±(0.8%+2)	±(0.8%+2)
AC Voltage	2V/20V/200V	±(0.8%+3)	±(0.8%+3)
	600V	±(1.2%+3)	±(1.2%+3)
DC Current	20mA	±(0.8%+1)	
	200mA	±(1.5%+1)	±(1.5%+1)
	10A	±(2.0%+5)	±(2.0%+5)
AC Current	20mA	±(1.0%+3)	
	200mA	±(1.8%+3)	±(1.8%+3)
	10A	±(3.0%+7)	±(3.0%+7)
Resistance	200Ω	±(0.8%+3)	±(0.8%+3)
	2KΩ/20KΩ/200KΩ/2MΩ	±(0.8%+1)	±(0.8%+1)
	20MΩ	±(1.0%+2)	±(1.0%+2)
	200MΩ	±(5.0%+10)	±(5.0%+10)
Capacitance	20nF/200nF/2μF/20μF	±(4.0%+3)	±(4.0%+3)
	200μF	±(5.0%+10)	±(5.0%+10)
Frequency	20KHz	±(1.5%+5)	
Temperature	-20°C~0°C	±(5.0%+4)	
	1°C~400°C	±(2.0%+3)	
	401°C~1000°C	±(2.0%+5)	
Inductance	20mH/200mH/2H/20H		±(3.0%+5)

Features

Display	counts	2000	2000
APO	Auto Power Off	●	●
NCV	Non-Contact Voltage Detector	●	●
Transistor hFE	0~1000	●	●
Diode	2.7V	●	●
Continuity Buzzer	≤30Ω	●	●
Data Hold		●	●
Display Backlight		●	●
LBD	Low Battery Display	●	●

General

Power Supply	1×9V6F22 Battery
Product Size	188mm×92mm×50mm/7.4"×3.6"×2.0"
Product Weight	380g/0.83lb
Safety Rating	CE ETL CAT III 600V RoHS

● Feature Difference