

DIGITAL MULTIMETER

MY70 / MY74

EMC
LVD



MY70

VOLTAGE AC 600V
DC 600V

CURRENT AC 10A
DC 10A



MY74

VOLTAGE AC 600V
AC 600V

CURRENT AC 10A
DC 10A



Specifications

MY70

MY74

Specifications	Range	Accuracy	
DC Voltage	200mV/2V/20V/200V	±(0.5%+2)	±(0.5%+2)
	600V	±(0.8%+2)	±(0.8%+2)
AC Voltage	200mV	±(1.2%+3)	
	2V/20V/200V	±(0.8%+3)	±(0.8%+3)
	600V	±(1.2%+3)	±(1.2%+3)
DC Current	20mA	±(0.8%+1)	±(0.8%+1)
	200mA	±(1.5%+1)	±(1.5%+1)
	10A	±(2.0%+5)	±(2.0%+5)
AC Current	2mA	±(1.0%+5)	±(1.0%+5)
	20mA	±(1.0%+5)	±(1.0%+5)
	200mA	±(1.8%+5)	±(1.8%+5)
	10A	±(3.0%+7)	±(3.0%+7)
Resistance	200Ω	±(0.8%+3)	±(0.8%+3)
	2KΩ/20KΩ/200KΩ/2MΩ	±(0.8%+2)	±(0.8%+2)
	20MΩ	±(1.0%+5)	±(1.0%+5)
	200 MΩ	±(6.0%+10)	±(6.0%+10)
Capacitance	2nF/20nF/200nF/2μF		±(4.0%+3)
	100μF		±(6.0%+10)
Frequency	20kHz		±(2.0%+5)
Temperature	-20°C~0°C		±(5.0%+4)
	1°C~400°C		±(2.0%+3)
	401°C~1000°C		±(2.0%+5)

Features

Display	counts	2000	2000
APO	Auto Power Off	●	●
Transistor hFE	0~1000	●	●
Diode	2.7V	●	●
Continuity Buzzer	<50Ω	●	●
Data Hold		●	●
LBD	Low Battery Display	●	●

General

Power Supply	1×9V 6F22 Battery
Product Size	188mm×93mm×50mm/7.4"×3.7"×1.96"
Product Weight	380g/0.84lb
Safety Rating	CE CAT III 600V RoHS

● Feature Difference