


DIGITAL MULTIMETER

MY75 / MY78

EMC
LVDCAT III
600V

MY75

VOLTAGE AC 600V

CURRENT AC 10A
DC 10A

MY78

VOLTAGE AC 600V
DC 600VCURRENT AC 10A
DC 10A

Specifications

MY75

MY78

Specifications	Range	Accuracy	
DC Voltage	200mV	±(0.05%+3)	
	2V/20V/200V	±(0.1%+3)	
	400mV/4V/40V/400V		±(0.7%+2)
	600V	±(0.15%+3)	±(0.8%+2)
AC Voltage	2V	±(0.5%+3)	
	20V/200V	±(0.8%+10)	
	400mV		±(3.0%+3)
	4V/40V/400V		±(0.8%+3)
	600V	±(1.0%+15)	±(1.2%+3)
DC Current	2mA	±(0.5%+50)	
	20mA	±(0.5%+50)	
	200mA	±(0.8%+50)	
	400μA/4mA/40mA/400mA		±(1.2%+3)
	10A	±(2.0%+10)	±(2.0%+5)
AC Current	2mA	±(0.8%+50)	
	20mA	±(0.8%+50)	
	200mA	±(1.2%+50)	
	400μA/4mA/40mA/400mA		±(1.5%+5)
	10A	±(2.5%+10)	±(3.0%+7)
DC Current (for Clamp Meter)	40A		±(0.8%+3)
	400A		±(0.8%+3)
AC Current (for Clamp Meter)	40A		±(1.0%+3)
	400A		±(1.0%+3)
Resistance	200Ω	±(0.5%+10)	
	2KΩ	±(0.3%+3)	
	20KΩ/200KΩ/2MΩ/20MΩ	±(0.3%+1)	
	400Ω/4KΩ/40KΩ/400KΩ/4MΩ		±(1.2%+2)
	200 MΩ	±(5.0%+10)	
	40 MΩ		±(2.0%+5)
Capacitance	2nF/20nF/200nF/2μF/100μF	±(4.0%+20)	
	4nF		±(4.0%+25)
	40nF/400nF/4μF/40μF/200μF		±(4.0%+15)
Frequency	9.999Hz/99.99Hz/999.9Hz/ 9.999kHz/99.99kHz/199.9kHz	±(2.0%+5)	±(2.0%+5)
	>200kHz	Take in only as reference	Take in only as reference
Duty Cycle	5%~95%		±(2.0%+2)
Features			
Display	counts	20000	4000
Auto Ranging	Auto & Manual		●
APO	Auto Power Off	●	●
REL	Relative Measurement		●
Transistor hFE	0~1000	●	●
Diode	2.7V	●	●
Continuity Buzzer	<50Ω	●	●
Data Hold		●	●
LBD	Low Battery Display	●	●
General			
Power Supply	1×9V 6F22 Battery	●	●
Product Size	188×93×50mm/7.4×3.7×1.96"	●	
	189×91×31.5mm/7.67×3.74×2.16"		●
Product Weight	380g/0.84lb	●	
	420g/0.92lb		●
Safety Rating	CE CAT III 600V RoHS	●	●

● Feature Difference